


Digital Power BTE with Dual ISP



mind440 is the first hearing aid on the market to introduce Dual Integrated Signal Processing

Moderate to severe-to-profound hearing losses

Suggested fitting range



Dual Integrated Signal Processing

- Dual layer integration of knowledge and performance
- Dynamic IntegratorTM
- Listening layer
- Awareness layer
- 15 frequency bands
- 15 compression channels

Main listening features

- HD LocatorTM
- Audibility ExtenderTM
- Multi-directional Active Feedback Cancelling
- Speech EnhancerTM
- TruSoundTM compression system with EDRC

Main awareness features

Fractal generator

- Fractal computation
- Melody composition

Signal integrity

- DAI auto-detect
- High definition program handling

Speech and sound synthesis

- SmartSpeakTM generator
- SmartTone generator

Hearing aid characteristics


- Optional remote control
- Optional volume control
- Program button
- Telecoil
- LED indication

mind440 m4-19

Maximum output - Ear simulator

IEC 60118-0


Output dB SPL



Maximum output - 2cc coupler

IEC 60118-7 / ANSI S3.22-2003


Output dB SPL



Output - Ear simulator

IEC 60118-0


Output dB SPL



Output - 2cc coupler

IEC 60118-7 / ANSI S3.22-2003

Output dB SPL



Technical data

Typical data obtained through standard pure tone measurements.

Hearing aid set to Compass Test mode 1, unless stated otherwise.

Measured using a normal hook and standard BTE coupler.

		IEC 60118-0	ANSI S3.22-2003 / IEC 60118-7
OSPL90	2500 Hz Peak Average	133 dB SPL 136 dB SPL 129 dB SPL	124 dB SPL 131 dB SPL 124 dB SPL
Acoustic output (Input 60 dB SPL)	2500 Hz Peak Average	118 dB SPL 121 dB SPL 110 dB SPL	108 dB SPL 115 dB SPL 105 dB SPL
Max gain (Input 50 dB SPL, Compass Max gain test mode)	2500 Hz Peak Average	69 dB 75 dB 65 dB	59 dB 70 dB 59 dB
Telecoil output (Input 10 mA/m)	2500 Hz Peak Average	110 dB SPL 113 dB SPL 100 dB SPL	100 dB SPL 106 dB SPL 97 dB SPL
Frequency range		100 Hz - 7100 Hz	100 Hz - 6850 Hz
Harmonic distortion (Input 70 dB SPL)	500 Hz 800 Hz 1600 Hz	2.2% 0.7% 0.2%	2.1% 0.5% 0.1%
Equivalent input noise		19 dB SPL	22 dB SPL
Battery drain (stand by)		0.8 mA	0.8 mA
Battery drain		0.8 mA	0.85 mA
Battery life / hours (Type 13 Zn-Air, 270 mAh)		330 (>265)	325 (>260)
Mobile phone immunity		IRIL: -11/-10 dB SPL	U-rating: M3 / T3

