


Behind-the-ear

15/10E/10/5E/5/3E/3



Fitting range



Minimal to severe-to-profound hearing losses

Key features	15	10E	10	5E	5	3E	3
Processing channels	15	10	10	5	5	3	3
Linked Feedback Cancellation	Linked	Linked	Linked	Linked	•	•	•
Automatic Adaptive Directionality	15 ch.	10 ch.	10 ch.	5 ch.	Broadband	Broadband	Broadband
Real-Input	•	•	•	•	•	•	•
Noise Reduction w. Speech Focus	•	•	•	•	•	Basic	Basic
Listening programs	5	4	3	3	3	3	3
Linked Volume/Program Control	•	•	•	•	•	•	•
EasyVoice/EasyTone	•	•	•	•	•	EasyTone only	EasyTone only
Zen/Zen+	Linked	Linked	Linked	Linked	ZEN (no Zen+)		
Sound Stabiliser	•	•	•	•	Basic	Basic	Basic
Wireless CROS compatible	•	•	•	•	•	•	
RearView	•	•	•	•			
Linear frequency transposition	•	•	•	•			
Real Ear effect	•	•					
Impulse Noise Rejection II	•	•					
Linked Speech Enhancement System	Linked	•					
Phone Stream	•	•					
Linked Compression	•						
Personal Zen	•						
Accessories							
App for iPhone, Android and new functionality	Via COM-DEX	Via COM-DEX	Via COM-DEX	Via COM-DEX	Via COM-DEX		
DEX accessories	•	•	•	•	•	RC-DEX only	

Colours

- 021
 Warm Beige
- 081
 Tan Silk
- 072
 Winter Silver
- 073
 Titan Grey
- 074
 Midnight Black
- 071
 Capp. Brown
- 069
 Summer Gold


BTE Behind-the-ear

15/10E/10/5E/5/3E/3


Technical data

		IEC 118-0	ANSI S3.22	
Output sound pressure level (Input 90 dB SPL)	2500 Hz	135	125	dB SPL
	Peak	137	132	dB SPL
	Average	130	125	dB SPL
Acoustic output (Input 60 dB SPL)	2500 Hz	121	111	dB SPL
	Peak	122	115	dB SPL
	Average	112	110	dB SPL
Full-on gain (Input 50 dB SPL)	2500 Hz	75	64	dB
	Peak	75	66	dB
	Average	63	59	dB
Telecoil output (Input 10 mA/m)	2500 Hz	109	99	dB SPL
	Peak	112	105	dB SPL
	Average	101	99	dB SPL
Frequency range		100 - 7700	100 - 6750	Hz
Total harmonic distortion (Input 70 dB SPL)	500 Hz	<2%	<2%	%
	800 Hz	<2%	<2%	%
	1600 Hz	<2%	<2%	%
Equivalent input noise level		17	20	dB SPL
Battery current (stand by)		0,92	0,92	mA
Battery current		0,97	1,20	mA
Battery life (Type 312 Zn-Air, 145 mAh)		150 (>125)	120 (>105)	h
Mobile phone immunity		IRIL: -22/-6 dB SPL	U-rating: M3/T2	


MAXIMUM OUTPUT - EAR SIMULATOR
IEC 118-0



MAXIMUM OUTPUT - 2CC COUPLER
ANSI S3.22 (2009)



OUTPUT - EAR SIMULATOR
IEC 118-0



OUTPUT - 2CC COUPLER
ANSI S3.22 (2009)

