


WIDEX ENJOY™ CIC-M WITH DUAL CORE PROCESSOR



The WIDEX CIC MICRO is based on the WIDEX ENJOY-platform, with a Widex dual core chip that handles automatic processing more accurately and faster than before. The non-wireless WIDEX CIC MICRO is perfect for clients who prefer the smallest possible and most discreet solution, with outstanding, automatic sound processing.

- Uses a size 10 battery
- Protection class IP68
- Minimal to severe hearing losses
- Preference Control via TONELINK App

SUGGESTED FITTING RANGE



STANDARD TECHNOLOGY

- ENJOY-platform with dual core processor
- Acclimatisation rationales
- Power Saver IV technology for low current consumption

KEY FEATURES	440	330	220	110
Performance	xxxxxxx	xxxxxxx	xxxxx	xxxx
Processing and fine-tuning channels	15	12	10	6


APPS FOR iOS AND ANDROID

TONELINK App				
	•	•	•	•


FEATURES

FEATURES				
Adaptation manager	•	•	•	•
Fluid Sound Analyser (sound classes)	11 (IE)	7 (IE)	4	3
High-frequency boost	•			
Speech Enhancer RT	IE	•		
TruSound Softener	•	•	•	
Soft-level noise reduction	•	•	•	•
Noise Reduction	•	•	•	•
Audibility Extender	•	•	•	•


MAXIMUM OUTPUT - EAR SIMULATOR




MAXIMUM OUTPUT - 2CC COUPLER



OUTPUT - EAR SIMULATOR



OUTPUT - 2CC COUPLER



Technical data:

Typical data obtained through standard pure tone measurements. Hearing aid set to Compass Reference Test Gain, unless stated otherwise. Measured using a standard ITE coupler without wax guard, and with a 5 x 1.55mm tube. For further information, please contact Widex at global.widex.com.

		EAR SIMULATOR IEC 60118-0:1983 + A1:1994	2CC COUPLER IEC 60118-0:2015 , ANSI S3.22-2014
OSPL90	1600 Hz	118 dB SPL	109 dB SPL
	Peak	124 dB SPL	114 dB SPL
	Average	118 dB SPL	110 dB SPL
Acoustic output (Input 60 dB SPL)	1600 Hz	103 dB SPL	94 dB SPL
	Peak	108 dB SPL	97 dB SPL
	Average	99 dB SPL	93 dB SPL
Full-on gain (Input 50 dB SPL, Compass Full-on gain)	1600 Hz	62 dB	53 dB
	Peak	63 dB	57 dB
	Average	61 dB	52 dB
Acoustic frequency range		100 Hz - 9700 Hz	100 Hz - 8800 Hz
Harmonic distortion	500 Hz	<2%	<2%
	800 Hz	<2%	<2%
	1600 Hz	<2%	<2%
Equivalent input noise		25 dB SPL	26 dB SPL
Battery drain (standby)		0.91 mA	0.91 mA
Battery drain*		0.93 mA	0.95 mA
Battery life (Type 10 Zn-Air, 170 mAh)*		110 h	105 h
Mobile phone immunity (IEC 60118-13:2016, ANSI C63.19:2011)		IRIL: -38/-33/-27 dB SPL	U-rating: M4

*Battery life in real-life situations depends among other things on the hearing aid features used, streaming time, and the quality of the battery used.

Do not modify this equipment without authorization of the manufacturer. Spare parts and instructions for correct repair can be acquired from Widex.