

WIDEX MAGNIFY™ RIC 10 WITH M-RECEIVER




The WIDEX RIC 10 is part of the WIDEX MAGNIFY™ family. Built around the WIDEX MAGNIFY™ platform to deliver better sound via TruAcoustics™ and all on a brand-new chip.

Fitting RIC 10 is easier than ever before, thanks to TruAcoustics™ giving a more powerful personalised sound.

- Multiple wireless connectivity via WidexLink technology and TONELINK App
- Compatible with the DEX assistive listening devices
- Uses an M-receiver
- Uses a size 10 battery
- Protection class IP68
- Mild to severe hearing loss

SUGGESTED FITTING RANGE



STANDARD TECHNOLOGY

- WIDEX MAGNIFY™ platform with Personal Gain Integrator
- TruAcoustics™ for improved sound and fitting

KEY FEATURES	100	50	30
Processing and fine-tuning channels	6	4	4
TruAcoustics™ with Personal Gain Integrator	•	•	•

CONNECTIVITY

WidexLink to DEX assistive listening devices*	•	•	
---	---	---	--

APPS FOR IOS AND ANDROID

TONELINK App	•	•	
COM-DEX App	•	•	


FEATURES

Adaptation manager	Auto	Auto	Manual
Programs	3	3	3
Locator	6 ch	4 ch	Omni/Front
Preference Control	•	•	
Soft-level noise reduction	•	•	•
Noise Reduction	NR	Minimal	Minimal
ZEN	•	•	
Audibility Extender	•		
CROS Support	•	•	


*Also includes DEX assistive listening devices: TV-DEX, COM-DEX, RC-DEX, FM+ DEX

For information regarding which devices WIDEX MAGNIFY, direct streaming, is compatible with, please go to: global.widex.com/compatibility


MAXIMUM OUTPUT - EAR SIMULATOR




MAXIMUM OUTPUT - 2CC COUPLER



OUTPUT - EAR SIMULATOR



OUTPUT - 2CC COUPLER



Technical data:

Typical data obtained through standard pure tone measurements. Hearing aid set to Compass Reference Test Gain, unless stated otherwise. Measured using a standard ITE coupler without wax guard. For further information, please contact Widex at global.widex.com

		EAR SIMULATOR IEC 60118-0:1983 + A1:1994	2CC COUPLER IEC 60118-0:2015, ANSI S3.22-2014
OSPL90	1600 Hz	118 dB SPL	109 dB SPL
	Peak	124 dB SPL	114 dB SPL
	Average	118 dB SPL	111 dB SPL
Acoustic output (Input 60 dB SPL)	1600 Hz	102 dB SPL	93 dB SPL
	Peak	108 dB SPL	98 dB SPL
	Average	98 dB SPL	93 dB SPL
Full-on gain (Input 50 dB SPL, Compass Full-on gain)	1600 Hz	63 dB	54 dB
	Peak	69 dB	59 dB
	Average	64 dB	56 dB
Acoustic frequency range		100 Hz - 10000 Hz	100 Hz - 9000 Hz
Harmonic distortion (typical)	500 Hz	<2%	<2%
	800 Hz	<2%	<2%
	1600 Hz	<2%	<2%
Equivalent input noise		22 dB SPL	22 dB SPL
Battery drain (standby)		0.98 mA	0.98 mA
Battery drain*		1.00 mA	1.02 mA
Battery life (Type 10 Zn-Air, 100 mAh)*		100 h	100 h
Mobile phone immunity (IEC 60118-13:2016, ANSI C63.19:2011)		IRIL: -39/-7/-4 dB SPL	U-rating: M4

*Battery life in real-life situations depends among other things on the hearing aid features used, streaming time, and the quality of the battery used.

Do not modify this equipment without authorization of the manufacturer. Spare parts and instructions for correct repair can be acquired from Widex.